

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A system, comprising:
  - a rendering apparatus;
  - a server; and
  - a network to enable communication between the rendering apparatus and the server;wherein the server provides access to server content that includes separately accessible content server items identified by respective server content locators;
- wherein the rendering apparatus provides access to local content wherein titles of the local content are associated with respective local content identifiers;
- wherein the rendering apparatus ~~is operative to render~~renders local content items of the local content and ~~to render~~renders server content items that relate to the local content items;

wherein the system ~~is operative to generate and to~~  
store, regenerate and stores a list of bookmarks, wherein each  
bookmark in the list of bookmarks includes a server content locator  
and a local content identifier to link a local content item to a  
related server content item; and

wherein the rendering apparatus ~~is operative to~~  
~~present~~presents the stored list of bookmarks to a user and ~~render~~  
renders a server content item indicated by the server content  
locator of a user-selected bookmark conditional on having access to  
a local content title associated with the local content identifier  
of the user-selected bookmark, wherein if there is no access to the  
local content title, the server content item can not be rendered.

2. (Previously presented) The system as claimed in claim 1,  
wherein the rendering apparatus includes a user interface for  
presenting to the user which bookmarks in the stored list of  
bookmarks are selectable at a given time for rendering of server  
content indicated by the respective bookmark at that time, wherein  
if a bookmark is not selectable, the bookmark is presented grayed  
to indicate that it is not selectable.

3. (Previously presented) The system as claimed in claim 1, wherein a bookmark is selectable only if the rendering apparatus has access to a local content title associated with the local content identifier of the bookmark and wherein access to the local content is determined based on a comparison with a hash of statistically unique data of the local content title.

4. (Previously presented) The system as claimed in claim 1, wherein the rendering apparatus includes a user interface for presenting bookmarks to a user organized according to the respective local content identifiers of the bookmarks.

5. (Currently amended) The system as claimed in claim 1, wherein the rendering apparatus ~~is operative to render~~renders both a server content item indicated by the server content locator of a user-selected bookmark in synchronization with rendering the local content title associated with the local content identifier of the bookmark in response to user selection of the user-selected bookmark.

6. (Previously presented) The system as claimed in claim 5, wherein separately accessible items of the local content are identified by respective local content locators, wherein the bookmark includes a local content locator enabling starting the rendering of the local content title at a location indicated by the local content locator.

7. (Previously presented) The system as claimed in claim 1, wherein the bookmark includes a user ID identifying a user of the rendering apparatus, or a family ID identifying a family of users of the rendering apparatus or both user and family IDs.

8. (Currently Amended) The system as claimed in claim 7, wherein the user interface ~~is operative to present~~presents the stored bookmarks organized according to the user ID or family ID of the bookmarks or both user and family IDs, wherein stored bookmarks that do not correspond to the user ID or the family ID are not presented.

9. (Currently amended) The system as claimed in claim 1, wherein the bookmark includes a parental level indicator, wherein the rendering apparatus ~~is operative to present~~presents a bookmark or ~~to render~~renders a remote item indicated by a bookmark, or ~~present~~and renderpresents and renders, only if the parental level indicator of the bookmark matches a parental level setting of the rendering apparatus.

10. (Currently amended) The system as claimed in claim 1, wherein the system ~~is operative to generate and store~~generates and stores a bookmark in the bookmark list in response to an instruction from a user, wherein the generated bookmarks each include a server content locator identifying a server content item currently being rendered and a local content identifier associated with a local content item that currently is accessible.

11. (Currently amended) The system as claimed in claim 1, wherein the system ~~is operative to generate~~generates bookmarks automatically.

12. (Currently amended) The system as claimed in claim 11,  
wherein the system ~~is operative to generate~~generates a bookmark for  
a server content item in response to an instruction to terminate  
rendering of a server content item to enable resumption of  
rendering of the server content item.

13. (Currently amended) The system as claimed in claim 11,  
wherein the system ~~is operative to generate~~generates a bookmark for  
a server content item in response to a user selecting a server  
content item for rendering, creating a history list of bookmarks,  
wherein the history list is assigned to a current user providing a  
personal history list for the user that is different than a  
personal history list for another user.

14. (Currently amended) The system as claimed in claim 1, wherein  
the rendering apparatus ~~is operative to verify~~verifies an  
authenticity of an accessible local content title and ~~to~~  
~~render~~renders a server content item indicated by the server content  
locator of a bookmark only upon a positive outcome of the  
verification the accessible local content title.

15. (Currently amended) The system as claimed in claim 1, wherein a local content title is stored on a removable storage medium including a medium identifier, wherein the local content identifier includes the medium identifier, wherein ~~access to the local content title is determined based on a comparison with~~ the rendering apparatus presents the stored list of bookmarks to the user and renders the server content item indicated by the server content locator of the user-selected bookmark conditional on having access to the medium identifier.

16. (Previously presented) The system as claimed in claim 1, wherein the rendering apparatus is operative to generate the bookmarks.

17. (Currently amended) The system as claimed in claim 1, wherein ~~the server is operative to store~~stores the bookmarks.

18. (Previously presented) A method of generating a bookmark to content in a server accessible through a network, the method comprising acts of:

retrieving a local content identifier associated with a title of a local content item that accessible for rendering by a rendering apparatus local to the local content item;

retrieving a server content locator identifying a separately accessible server content item that is related to the local content title;

generating and storing a new bookmark in a list of bookmarks to link the local content item to the related server content item, wherein the new bookmark includes the retrieved server content locator and corresponding local content identifier; and

presenting the list of bookmarks, wherein if a bookmark on the list of bookmarks is not selectable, the bookmark is presented grayed to indicate that it is not selectable.

19. (Previously presented) A method of accessing content in a server accessible through a network; the method including acts of:



presenting a list of bookmarks to a user enabling user-selection of one or more bookmarks in the presented list of bookmarks, wherein each bookmark in the list of bookmarks includes a local content identifier associated with a local content title of a local content item accessible for rendering by a rendering apparatus local to the local content item, and a server content locator identifying a separately accessible server content item that is related to the local content title of the local content item; and

in response to a user-selected bookmark in the presented list of bookmarks, rendering a server content item indicated by the server content locator of the user-selected bookmark conditional on having access to the local content title associated with the local content identifier of the user-selected bookmark, wherein if there is no access to the local content title, the server content item can not be rendered.

20. (Previously presented) A computer readable memory medium comprising program instructions stored thereon, which are executable by a processor to cause the processor to:

present a list of bookmarks to a user enabling user-selection of one or more bookmarks in the presented list of bookmarks, wherein each bookmark in the list of bookmarks includes a local content identifier associated with a local content title of a local content item accessible for rendering by a rendering apparatus local to the local content item, and a server content locator identifying a separately accessible server content item that is related to the local content title of the local content item; and

in response to a user-selected bookmark in the presented list of bookmarks, render a server content item indicated by the server content locator of the user-selected bookmark conditional on having access to the local content title associated with the local content identifier of the user-selected bookmark, wherein if there is no access to the local content title, the server content item can not be rendered.